



FA-17LCM-AV 17" LCD Monitor



Fujitsu 17" AV LCD display offers a simple sleek design, high quality picture image at very affordable price. It's slim and simple black body suits any type of desktop and also to maximise your desktop area. It is perfect for security applications.

Comes with:

- 1 x User manual
- 1 x AC power cord
- 1 x D-Sub15pin VGA cable
- 1 x PC Audio Cable

Ordering Information

| SKU | Description |
|--------|-----------------------------|
| 610456 | FA-17LCM-AV 17" LCD Monitor |

- ▶ Flat panel LCD TFT (Active Matrix)
- ▶ Built-in A/V Connectors with BNC Video Input, ideal for security application
- ▶ Narrow design with slim bezel
- ▶ Fast response time
- ▶ Stereo Speakers
- ▶ Aspect ratio 4:3
- ▶ Support DDC 1/2B and Windows PNP Plug & Play
- ▶ Wall and arm mountable
- ▶ External Power Supply

Technical Specifications

Display Feature

| | |
|------------------|-------------------------------------|
| Aspect ratio: | 4 : 3 |
| LCD panel: | a-SI TFT-LCD (SXGA) |
| Display size: | 337.92H x 270.34Vmm |
| Resolution: | 1280 (H) x 1024 (V) RGB |
| Dot Pitch: | 0.264 (H) x 0.264 (V) mm |
| Max. Colours: | 16.2M |
| Horizontal Freq: | 30K ~ 80KHz |
| Vertical Freq: | 56 ~ 75Hz |
| Brightness: | 300 cd/m ² |
| Contrast: | 500: 1 |
| Viewing Angle: | 70/60/75/75 (UP/DOWN/LEFT/RIGHT) |
| Response Time: | 8ms |

Audio Speaker System

| | |
|--------------------------|----------------|
| Speaker Type: | Undetachable |
| Max/ Audio Output: | 2W x 2 |
| Sound Multiplex Circuit: | Spatial stereo |

Terminals

| | |
|--------------------|-----------------------------|
| Signal Input Port: | D-Sub - BNC - S-Video |
| Audio IN: | PC Audio in 3.5mm jack |
| Audio OUT: | Line Out Speaker 3.5mm jack |

| | |
|----------------------------------|-----------------------|
| Power Supply: | DC 12V |
| Power Consumption: | 30W |
| Stand by Mode Power Consumption: | 3W or less |
| Approvals: | CE, C-tick |
| Package Dimensions: | 150W x 404H x 380D mm |
| Operating Temperature: | 0° ~ 50° |
| Operating Humidity: | 20% ~ 90% |
| Storage Temperature: | -20° ~ 60° |
| Storage Humidity: | 5% ~ 90% |